

# TTR-173WE Ribbon – Technical Data Sheet

## Product Data

### Storage:

**Shelf life:** 3 Years

Temperature >0° to 40°C Max

### Compatible Printers

300 DPI Printer      STP-SQX-300M-S-NC-S  
STP-XD4T-300-S-NC-S  
STP-EOS5-300-S-NC-S

### Material:

**Resin based White ink. polyester film with anti-static backing film.**

## Application Method – Stick on

The TTR-173 ribbon is a high-performance resin ink ribbon used to print directly onto recommended Sumitag labels.

- High Print Performance
- One colour - White
- Antistatic carrier film to help protect the printer
- Automotive Grade Pigmented Resin



Property	Value	Test Method
Ink Coating Weight	4.57 g/sq.M	
Ink Melting Temperature	>100°C	
Print Optical Density	>.38	Macbeth RD-918
Ribbon Transmission	>.85	Tobias TBX-IR
Barcode Print Contrast Signal	98%	PSC Quickcheck 500
Print Gloss	>80%	Macbeth Novo-gloss 60° Glossmeter

# TTR-173WE Ribbon – Technical Data Sheet

## Ordering Information

mm	Length m	Core Size mm	Order Code
50mm	300	25.4	TTR-050-300-WE-173
82mm	300	25.4	TTR-082-300-WE-173

- Other sizes available MOQ's apply, please contact your SEI representative for more information.

## Business Management Accreditations

