

# LF Silicone Sleeving – Technical Data Sheet

## Product Data

### Storage:

Cool dry place out of direct sunlight

### Material:

Silicone

### Operating Temperature:

-65°C to +220°C

## Application Method – Slide on

LF grade silicone sleeving exhibits great resilience and elasticity, retaining these properties over a wide temperature range. While normal operating temperatures can be as high as 220°C, LF grade silicone tubing will remain flexible at temperatures as low as -65°C.

- Self Extinguishing
- Excellent resistance to chemicals
- Pre-cut and Spiral Cut forms available
- Outstanding Electrical Insulation
- Available in 11 Colours
- Conforms to BS4G198 Type 3 dimensions
- Conforms to Airbus NSA937201 MA
- Available in multiple formats (see order information)



Property	Value	Test Method
Resistance to extreme of Temperatures.	-65°C to +220°C	BS:4G198 T3
Shore Hardness (A)	40-55° SH	BS EN 60684-3
Tension set	Max 25%	BS:4G198 T3
Tensile strength	8 MPa minimum	
Elongation at break (extensibility after ageing)	550% typical value (min. of 50% absolute elongation)	BS:4G198 T3
Fluid resistance	Pass (all fluids)	BS4G198 T3
Voltage Proof	No Breakdown	BS4G198 T3
Circumferential ext. (aged and unaged)	Pass	BS4G198 T3
Finish and colour	Pass	BS4G198 T3
Low Temp. Flexibility	Pass	BS4G198 T3
Flammability	Pass (Time to extinguish <30s) (Afterburn length <100mm)	BS4G198

# LF Silicone Sleeving – Technical Data Sheet

## Ordering Information

## Plain Silicone Sleeving

Product Reference	Nominal Bore ID (mm)	Nominal Wall Thickness (mm)	Length
LFP05/05	0.5	0.5	Any Length to nearest 0.5mm
LFP075/05	0.75	0.5	
LFP10/05	1.0	0.5	
LFP15/05	1.5	0.5	
LFP20/05	2.0	0.5	
LFP25/05	2.5	0.5	
LFP30/05	3.0	0.5	
LFP40/05	4.0	0.5	
LFP50/05	5.0	0.5	
LFP75/07	7.5	0.7	
LFP100/07	10.0	0.7	

## Marked Silicone Sleeving

Product Reference	Nominal Bore ID (mm)	Nominal Wall Thickness (mm)	Length
LFM05/05	0.5	0.5	Any Length to nearest 0.5mm
LFM075/05	0.75	0.5	
LFM10/05	1.0	0.5	
LFM15/05	1.5	0.5	
LFM20/05	2.0	0.5	
LFM25/05	2.5	0.5	
LFM30/05	3.0	0.5	
LFM40/05	4.0	0.5	
LFM50/05	5.0	0.5	
LFM75/07	7.5	0.7	
LFM100/07	10.0	0.7	

Available formats: Continuous Sleeving, Cut Sleeves, Pre-lubricated, Spiral cut, slit cut, Par-o-cut, Printed Markers, Kit Boxes

Colours available:

Standard resistor colour coded - Black (BK), Brown (GN), Red (RD), Orange (OR), Yellow (YW), Green (GN), Blue (BE), Violet (VT), Grey (GY), White (WE), Pink (PK)

Non-standard – Transparent (TR)

## Business Management Accreditations



Registered in England No. 412829

©2023 SEI Identification Solutions Limited. All rights reserved. The information on this datasheet is provided for general information only. Although we make reasonable efforts to update the information on this datasheet, we make no representations, warranties or guarantees, whether express or implied, that the content of the datasheet is accurate, complete, or up to date. Users are advised to ensure that each product meets their own requirements, and we will not be liable for any loss or damage arising in connection with your use of or reliance on any information contained in this datasheet. Specifications given in this data sheet are subject to change without notice.